

Pro800D[™] Hi-Power Wire and Valve Locator







Pro800D™ Features

- 8 D Cell Transmitter Power
- Wireless Broadcast Cable Connection
- Triple AC Buzz/Noise Rejection
- 20% More Power
- Totally New Wand Design
- Null or Peak Reception Modes

PRODUCT DESCRIPTION

The Pro800D[™] builds on the innovative features introduced with the Pro800[™]. The Pro800D[™] adds the flexibility of using 8 D cell batteries for transmitter power.

In addition, we have kept the unique features offered by the original Pro800[™], including wireless inductive connection to cables, 20% more power, excellent wand noise rejection, and null/peak reception modes.

With added power and AC noise rejection, the standard locate becomes the clear, powerful locate. Go farther, go faster, and go clearer than ever before.

Wireless connection means inducing tracing signal all through the ground, allowing the user to trace any conductor in the ground within 25-30 feet of the transmitter. Once the cable picks up the signal, track it for up to hundreds of feet. When it dies, relocate your transmitter to the lost spot and start again. Voila, infinite distance capability!

PRODUCT FEATURES

- · Ergonomic, Light Wand Design
- Membrane Switch Technology
- Low Battery and Power LEDs
- Unlimited Tracking Distance in Wireless/Broadcast Mode
- Audio or Analog Meter Response Indicator
- Null or Peak Tracking

SPECIFICATIONS

Power Requirements: Transmitter uses 8 D Cell batteries / Receiver uses 1 9v square

Maximum Ranges: Depth at 8 Feet, Distance is infinite with Wireless/Broadcast Mode

Frequencies: Standard Mode @ 2Khz / Wireless Mode @ 185khz

Power Output Max: 900v p-p

ORDERING INFORMATION

CAT NO. Pro800D™

DESCRIPTION
Wire and Valve Locator

QUANTITY 1



For more information contact:

Armada Technologies 8535 Byron Commerce Dr. SW Suite A

Byron Center, MI 49315

Phone: (616) 803-1080 Fax: (616) 803-1083 www.armadatech.com

Rev. 4 Pro800D-01240 ©2024